

HYUNDAI

DP158CCS



GENERATOR



15.1L / 8 CYLINDERS



EPA TIER2

DESCRIPTION

- HD Construction Equipment introduced new generator electronic engines DP158C- Series.
- When compared to other engines of equivalent capacity, it displays a higher output, better fuel efficiency, higher safety, and easier maintenance.
- Achieving precise fuel delivery with common rail system and electronic control unit(ECU), it allows optimal injection timing and pressure based on engine's current operating conditions.



FEATURES & BENEFITS

[High Performance & Durability]

- G3 Class(ISO 8528-5)
- HVO/GTL : Usable up to 100%
- Robust main structure parts
- Oil maintenance interval: 500 hrs without replenishment
- Operates without power derating up to an altitude of 1,000 meters
- Longer warranty period through strict verification

[Convenience & Safety]

- Maintenance free through auto tensioning belt drive system
- Cold Startability@-10°C without supplementary device
- Radiator to cover a wide range of usage condition
- Safety guard for hazard parts
- Meet REACH & RoHS regulations

OUTPUT

1,500 RPM (50Hz)									1,800 RPM (60Hz)								
Standby			Prime/DCP			Continuous			Standby			Prime/DCP			Continuous		
kWm	kWe	kVA	kWm	kWe	kVA	kWm	kWe	kVA	kWm	kWe	kVA	kWm	kWe	kVA	kWm	kWe	kVA
-	-	-	-	-	-	-	-	-	618	558	698	562	506	633	393	346	433

- Generator efficiency (typical) : 94.5%
- kWm= kilo Watt mechanical, Gross power
- kWe= kilo Watt electric = (kWm-Fan loss) x Generator eff. / kVA= kilo Volt Ampere
- Calculations based on a 0.8 power factor = kWe/0.8
- U.S. EPA TIER 2 Nonroad emission for Stationary Emergency Use Only. Prime/DCP/Continuous power rating for reference only.

DP158CCS

GENERAL DATA

Type	Diesel, Water cooled, Turbo charged & Intercooled
Bore	128 mm
Stroke	147 mm
Displacement liter	15.1 liter
Cylinders and Arrangement	Cast iron, 8 Cylinder, V type(90°)
Battery charging alternator	27.5V x 45A
Starting voltage	24V
Fuel system	Common rail, Direct injection controlled by ECU
Fuel filter	Full flow, Cartridge type
Lube oil filter type (s)	Full flow, Cartridge type
Lube oil capacity (l)	Max. 55 liters , Min. 22 liters
Flywheel dimensions	SAE NO.1M / Clutch NO.14M

COOLING SYSTEM

Cooling method		Fresh water forced circulation
Cooling ratio		50% ethylene glycol; 50% water
Water capacity (L)	with radiator	72 liters
	without radiator	27 liters
Fan power (kW)		27 kW (1,800 rpm)
Cooling system air flow (m³/min)		733.9 m³/min (1,800 rpm)


FUEL CONSUMPTION

1,500 RPM (50Hz)		
%	kWm	Liters/hr
Standby		
100	-	-
Prime		
100	-	-
75	-	-
50	-	-
25	-	-
Continuous		
100	-	-

1,800 RPM (60Hz)		
%	kWm	Liters/hr
Standby		
100	618.0	155.5
Prime		
100	-	-
75	-	-
50	-	-
25	-	-
Continuous		
100	-	-

DP158CCS

DIMENSIONS



Weights and Dimensions (G-Pack)

Radiator Type	Length – A	Width – B	Height – C	Dry Weight
Ex-Tropical	2,095 mm	1,570 mm	1,787 mm	1,644 kg
Tropical	2,091 mm	1,416 mm	1,700 mm	1,612 kg

POWER RATING GUIDE

ESP(STANDBY POWER) is applicable for supplying emergency power for the duration of the utility power outage. No overload capability is available for this rating. A standby rated engine should be sized for a maximum of an 70% average load factor and 500 hours of operation per year. This includes less than 25 hours per year at the Standby Power rating.

※ Specifications are subject to change without prior notice.